


微纳光子结构教育部重点实验室(复旦大学) Key Laboratory of Micro- and Nano-Photonic Structures (Fudan University), Ministry of Education


# Optimize performance of diffractive neural network by controlling the Fresnel number


Minjia Zheng<sup>1</sup>, Lei Shi<sup>1,\*</sup> and Jian Zi<sup>1</sup>


\*lshi@fudan.edu.cn

State Key Laboratory of Surface Physics, Key Laboratory of Micro- and Nano-Photonic Structures (Ministry of Education) and Department of Physics, Fudan University, Shanghai 200433, China











(a) MNIST handwritten digit and light distribution at the output plane. (b) The confusion matrix and energy distribution percentage of numerical simulation (97.08%) and experimental results (92.70%).



and the equivalent diffraction matrix of (c) deep and (d) single-layer DNN at different Fresnel numbers.

Matrix should: Many-to-one mapping and the arbitrariness Control the Fresnel number (the diffraction process) Solution:

### Experimental setup



Accuracy of single-layer DNN at different Fresnel numbers.

## Conclusion

We propose a new approach that controlling the diffraction related parameter, which is the Fresnel number, can improve the network's capability of expression and optimize the performance of DNN.

We implement DNN at visible range and experimentally tested the performance of single-layer DNN (got an accuracy of 92.70%).

Photonics Research, vol. 10, no. 11, 2022, pp. 2667-2676.





#### 微纳光子结构教育部重点实验室(复旦大学) Key Laboratory of Micro- and Nano-Photonic Structures (Fudan University), Ministry of Education


# Optimize performance of diffractive neural network by controlling the Fresnel number


Minjia Zheng<sup>1</sup>, Lei Shi<sup>1,\*</sup> and Jian Zi<sup>1</sup>


\*lshi@fudan.edu.cn

State Key Laboratory of Surface Physics, Key Laboratory of Micro- and Nano-Photonic Structures (Ministry of Education) and Department of Physics, Fudan University, Shanghai 200433, China











(a) MNIST handwritten digit and light distribution at the output plane. (b) The confusion matrix and energy distribution percentage of numerical simulation (97.08%) and experimental results (92.70%).



and the equivalent diffraction matrix of (c) deep and (d) single-layer DNN at different Fresnel numbers.

Matrix should: Many-to-one mapping and the arbitrariness Control the Fresnel number (the diffraction process) Solution:

### Experimental setup



Accuracy of single-layer DNN at different Fresnel numbers.

## Conclusion

We propose a new approach that controlling the diffraction related parameter, which is the Fresnel number, can improve the network's capability of expression and optimize the performance of DNN.

We implement DNN at visible range and experimentally tested the performance of single-layer DNN (got an accuracy of 92.70%).

Photonics Research, vol. 10, no. 11, 2022, pp. 2667-2676.

